

Paint Protect manual

Betonlook.nl's Paint Protect is most suitable for applying an extra effect to the surface in combination with our Metallic pigments. Mix the Paint Protect powder thoroughly with the specified water, let it set for 15 minutes and finally add the Metallic pigments.

Preparation

Apply the layer of Paint Protect after the underlying paint layer has dried for at least 24 hrs.

Applying the Paint Protect

Step 1: dilute the Paint Protect with water. For every 50 grams of Paint Protect, use 500 ml of water. Add the water in parts to the Verf Protect and stir well with a whisk.

Step 2: let the mixture rest for 15 minutes.

Step 3: stir the Paint Protect again, with a whisk. If you want to make sure there are no lumps, pass the Paint Protect through a strainer. When you're left with some lumps, you can dilute them with a little water and add them to the rest of the mixture. Make sure you have a smooth mixture without lumps before you start applying.

Are you going to mix the Paint Protect with Metallic pigments? Then add these pigments after step 3 and stir well.

Step 4: the Paint Protect is now ready to be applied. You can do this with the wide brush of 3 x 14 cm. Always apply the Paint Protect in only one layer.

Step 5: let the Paint Protect dry for 5 days.

Shelf life

Paint Protect from Betonlook.nl has an unopened shelf life of 6 months. Provided you store it in a dry environment, at a temperature between 10°C and 30°C.

Practical tips

- Paint Protect is not suitable against grease splashes. Because of this, we don't recommend using it in a kitchen.
- Paint Protect seals off many of our types of paint. In spaces where our paint is supposed to breathe, we advise against the Paint Protect. Think of spaces with a high humidity level, such as a bathroom/kitchen.
- Is the Paint Protect properly dry? Only clean the treated surface with a slightly damp cloth, because Paint Protect is water-repellent but not waterproof.
- Do not use chemical cleaners, as this will damage the protective layer. Even more important: it's better for the environment.
- Apply the Paint Protect to the surface in one go. This is because it dries rapidly and it will prevent you from applying double layers. (We don't recommend applying multiple layers.)